

Application No. 09/916,364
Amendment dated October 15, 2004
Reply to Office Action of August 25, 2004

Docket No. 4450-04/1P
Art Unit: 2839
Page 2 of 15

CLAIM SET AS AMENDED

1. (Currently Amended) An insert removably provided within a fiber optic cable management tool having at least one arcuate portion, comprising:

at least one curved member having a curved portion; and

the at least one curved member of the insert facing the at least one arcuate portion of the fiber optic cable management tool when the insert is provided within the fiber optic cable management tool, thereby forming

a channel formed having two sides along a length thereof, between one side being the at least one arcuate portion of the fiber optic cable management tool and an opposite side being the at least one curved member of the insert,

the channel having a radius that exceeds the minimum bend radius of a fiber optic cable to be provided in the fiber optic cable management tool.

2. (Original) An insert as recited in claim 1, wherein the channel has a radius that exceeds the minimum bend radius of a fiber optic cable having a diameter less than or equal to 1.7 millimeters.

3. (Original) An insert as recited in claim 1, wherein the channel formed by the curved portion of said at least one curved member and the arcuate portion of the fiber optic

Application No. 09/916,364
Amendment dated October 15, 2004
Reply to Office Action of August 25, 2004

Docket No. 4450-0411P
Art Unit: 2839
Page 3 of 15

cable management tool has a smaller width than a channel provided in the fiber optic cable management tool.

4. (Original) An insert as recited in claim 1, wherein the channel formed by the curved portion of said at least one curved member and the arcuate portion of the fiber optic cable management tool changes orientation of the fiber optic cable to be provided in the fiber optic cable management tool.

5. (Previously Presented) A fiber optic cable guiding insert, comprising:

a first curved member having first and second curved portions, the first curved portion of said first curved member having a radius that exceeds a minimum bend radius of a fiber optic cable to be guided by the insert;

a second curved member having first and second curved portions, the first curved portion of said second curved member having a radius that exceeds the minimum bend radius of the fiber optic cable; and

a third curved member having first and second curved portions which join each other at a point between the first curved member and the second curved member, wherein the second curved portion of said first curved member and the first curved portion of said third curved member form a first channel having a radius that exceeds the minimum bend radius of the fiber optic cable, and the second curved portion of said second curved member and the

*Application No. 09/916,364
Amendment dated October 15, 2004
Reply to Office Action of August 25, 2004*

*Docket No. 4450-0411P
Art Unit: 2839
Page 4 of 15*

second curved portion of said third curved member form a second channel having a radius that exceeds the minimum bend radius of the fiber optic cable.

6. (Previously Presented) A fiber optic cable guiding insert as recited in claim 5, wherein said first, second, and third curved members are integrally connected.

7. (Original) A fiber optic cable guiding insert as recited in claim 5, wherein the first curved portion of said first curved member, the first curved portion of said second curved member, and the first and second channels have radii that exceed the minimum bend radius of a fiber optic cable having a diameter less than or equal to 1.7 millimeters.

8. (Currently Amended) A fiber optic cable guiding insert, comprising:

at least one curved member having first, second, and third curved portions, and a flange at a distal end of the first and the second curved portions, the first, second, and third curved portions having radii that exceed a minimum bend radius of a fiber optic cable to be guided by the insert, wherein at least two of the curved portions are being concave-shaped and are joined at the flange.

Application No. 09/916,364
Amendment dated October 15, 2004
Reply to Office Action of August 25, 2004

Docket No. 4450-0411P
Art Unit: 2839
Page 5 of 15

9. (Original) A fiber optic cable guiding insert as recited in claim 8, wherein the first, second, and third curved portions have radii that exceed the minimum bend radius of a fiber optic cable having a diameter less than or equal to 1.7 millimeters.

10. (Currently Amended) A fiber optic cable management system, comprising:
at least one fiber optic cable management tool having a base portion, ~~at least one a~~
first arcuate portion and a second arcuate portion disposed on the base portion, and a
protruding member extending from the base portion to permit manual grasping of said at
least one fiber optic cable management tool; and

at least one insert removably provided ~~within~~ between the first and the second arcuate
portions of said at least one fiber optic cable management tool and having at least one curved
member having a curved portion; and

a channel formed between the ~~at least one first~~ first arcuate portion of said at least one
fiber optic cable management tool and the at least one curved member of the insert, the
channel having a radius that exceeds the minimum bend radius of a fiber optic cable to be
provided within the channel.

11. (Original) A fiber optic cable management system as recited in claim 10,
wherein the channel has a radius that exceeds the minimum bend radius of a fiber optic cable
having a diameter less than or equal to 1.7 millimeters.

Application No. 09/916,364
Amendment dated October 15, 2004
Reply to Office Action of August 25, 2004

Docket No. 4450-0411P
Art Unit: 2839
Page 6 of 15

12. (Original) A fiber optic cable management system as recited in claim 10, wherein the channel formed by the curved portion of said at least one curved member and the arcuate portion of said at least one fiber optic cable management tool has a smaller width than a channel provided in said at least one fiber optic cable management tool.

13. (Original) A fiber optic cable management system as recited in claim 10, wherein the channel formed by the curved portion of said at least one curved member and the arcuate portion of said at least one fiber optic cable management tool changes orientation of the fiber optic cable to be provided in said at least one fiber optic cable management tool.

14. (Currently Amended) A method of reducing a width of a channel provided in a fiber optic cable management tool, comprising

providing the fiber optic cable management tool having a channel between a first arcuate portion and a second arcuate portion thereof;

providing an insert within between the first arcuate portion and the second arcuate portion of the fiber optic cable management tool, the insert having at least one curved member which provides a second channel between the curved member of the insert and an arcuate portion of the fiber management tool, the second channel reducing the width of the channel provided in the fiber optic cable management tool, the second channel being a

*Application No. 09/916,364
Amendment dated October 15, 2004
Reply to Office Action of August 25, 2004*

*Docket No. 4450-0411P
Art Unit: 2839
Page 7 of 15*

reduced-width channel having a radius that exceeds the minimum bend radius of a fiber optic cable to be provided within the reduced-width channel.

15. (Original) A method of reducing a width of a channel provided in a fiber optic cable management tool as recited in claim 14, wherein the reduced-width channel has a radius that exceeds the minimum bend radius of a fiber optic cable having a diameter less than or equal to 1.7 millimeters.

16. (Original) A method of reducing a width of a channel provided in a fiber optic cable management tool as recited in claim 14, wherein the reduced-width channel may retain a fiber optic cable having a diameter less than or equal to 1.7 millimeters.

17. (New) An insert as recited in claim 11, wherein the at least one arcuate portion of the fiber optic cable management tool includes a first arcuate portion and a second arcuate portion, and

wherein the insert restricts a space between the first arcuate portion and the second arcuate portion of the fiber optic cable management tool.

18. (New) A fiber optic cable management system as recited in claim 10, wherein a width of the channel formed between the first arcuate portion of said at least one fiber optic

*Application No. 09/916,364
Amendment dated October 15, 2004
Reply to Office Action of August 25, 2004*

*Docket No. 4450-0411P
Art Unit: 2839
Page 8 of 15*

cable management tool and the at least one curved member of the insert is less than a distance between the first arcuate portion and the second arcuate portion of the fiber optic cable management tool.

19. (New) A fiber optic cable management system as recited in claim 10, wherein the insert restricts a space between the first arcuate portion and the second arcuate portion of the fiber optic cable management tool.

20. (New) A method of reducing a width of a channel provided in a fiber optic cable management system as recited in claim 14, wherein the step of providing an insert restricts a space between the first arcuate portion and the second arcuate portion of the fiber optic cable management tool.